




## Clamp seal CLAMP



### DESCRIPTION


- Clamp type A (with lip)
- Clamp type C (without lip)
- Rotationally symmetrical sealing rings
- Material: EPDM, VMQ, XP

### FUNCTION

- For installation spaces in accordance with DIN 32676, among others
- Production of fast and secure flange connections in continuously operated systems
- Static sealing by axial compression in the installation space

### PRODUCT ADVANTAGES

- Easy assembly and disassembly
- Ideal for flange connections that need to be opened more frequently
- Market-leading, proprietary design with the widest range of applications in all industries and for a variety of requirements
- Highest quality, durability and safety
- Best results in total cost of ownership



### APPLICATIONS

- Flanges in the process industry

### APPLICATION LIMITS

- Permissible maximum values depending on the other operating conditions, see technical manual.

### MEDIA RESISTANCE

- Please refer to resistance information in the chemical resistance guide at [www.fst.com](http://www.fst.com).

### CONFORMITY AND CERTIFICATES

- Please consult the material data sheet valid for the respective material for current information on approvals and certificates, as this information depends on the compound and cannot be listed exhaustively here.

### DESIGN GUIDELINE

- Please refer to the technical manual for design guidelines.

### INSTALLATION GUIDELINE

- The prerequisite for perfect function of the seal is careful installation in accordance with the technical manual.

### STORAGE ADVISE

- Storage temperature <25°C
- No direct heat sources
- No direct sunlight
- No condensation in the storage room
- No exposure to ozone or ionizing radiation
- Recommendations based on the revision of ISO 2230 dated 16.09.1992