

Technical data sheet in accordance with ASTM

Material 70 NBR N707D

black

cross linking: sulfur

revision index 1	revision date 10/1/2021		page	1/2
Physical properties		nominal range	typical values	
Hardness ASTM D2240, Shore A		70 ±5	69	Shore
Tensile strength ASTM D412		> 10	13.95	MPa
Elongation at break ASTM D412		> 200	276	%

Temperature range -25°C to 110°C

Declarations of conformity No data found!

Freudenberg

Freudenberg FST GmbH Technology&Innovation Material Compliance

Telefon: -Fax: -

Email: MaterialCompliance@fst.com



Technical data sheet in accordance with ASTM

Material 70 NBR N707D

black

cross linking: sulfur

revision index	revision date		
1	10/1/2021	page	2/2

Tested after ASTM D 2000: M 2 BG 710 B14 EO14 EO34

			nominal range	typical values
	Hardness	Shore	70 ±5	69
	Tensile strength	MPa	min. 10	13.95
	Elongation at break	%	min. 250	276
A14	Change after aging in Air 70h/100°C			
	Hardness	Shore A		2
	Tensile strength	%		10
	Elongation at break	%		-10
B14	Compression set 22h/100°C	%	25	7
EO14	Change after aging in IRM 901 70h/100°C			
	Hardness	Shore A	-5 to 10	4
	Tensile strength	%	-25	16
	Elongation at break	%	-45	3
	Volume	%	-10 to 5	-9.8
EO34	Change after aging in IRM 903 70h/100°C			
	Hardness	Shore A	-10 to 5	-2
	Tensile strength	%	-45	9
	Elongation at break	%	-45	-5
	Volume	%	0 to 25	0.4

The given values are based on a limited number of tests on standard test pieces (2mm sheets). The data from finished parts can deviate from above values depending on the manufactories process and the component geometry.

The data represents our present empirical values. It is incumbent on the person placing the order to examine whether it is suitable for its intended purpose, before using the product. All questions regarding the guarantee of this product are in line with our terms and conditions, inasmuch as statutory provisons do not plan for something else.

Freudenberg

Freudenberg FST GmbH Technology&Innovation Material Compliance

Telefon: -Fax: -

Email: MaterialCompliance@fst.com