

Material

71 ACM 112144

black

revision index

1

revision date

9/24/2009

page

1 / 3

Physical properties

	nominal range	typical values	
Density DIN EN ISO 1183-1, 23 °C	---	1.36	g/cm ³
Hardness DIN ISO 7619-1, Shore A, 23 °C	---	68	Shore
Modulus 100 %, DIN 53504, S2, 23 °C	---	9.4	MPa
Tensile strength DIN 53504, S2, 23 °C	---	11.4	MPa
Elongation at break DIN 53504, S2, 23 °C	---	188	%

Declarations of conformity

This overview is purely informative and does not constitute a declaration of conformity (DoC). Please refer to the actual declaration of conformity (DoC) including the conditions and its validity period.

	Country	Part	Remark	Expires
Info ROHS and ELV			EU 2000/53 (ELV) including EU 2011/65 and EU2015/863 (ROHS III)	see DoC

Freudenberg

Freudenberg FST GmbH
Technology&Innovation
Material Compliance

Telefon: -

Fax: -

Email: MaterialCompliance@fst.com

Material

71 ACM 112144

black

revision index

revision date

1

9/24/2009

page

2 / 3

Tested after ASTM D 2000: M 5 DH 706 A26 B16 EO16 EO36 F13

		nominal range	typical values
Hardness	Shore	70 ±5	69
Tensile strength	MPa	min. 6	8.9
Elongation at break	%	min. 100	180
A26 Change after aging in Air 70h/150°C			
Hardness	Shore	10	6
Tensile strength	%	-25	20
Elongation at break	%	-30	-27
B16 Compression set 22h/150°C			
	%	60	54
EO16 Change after aging in IRM 901 70h/150°C			
Hardness	Shore	-5 to 10	3
Tensile strength	%	-20	18
Elongation at break	%	-40	-5
Volume	%	±5	-2
EO36 Change after aging in IRM 903 70h/150°C			
Hardness	Shore	-15	-5
Tensile strength	%	-40	5
Elongation at break	%	-40	16
Volume	%	25	11
F13 Low-temperature resistance after 3 min at -10 °C 3min./-10°C			
		pass	pass

The given values are based on a limited number of tests on standard test pieces (2mm sheets) produced in the laboratory. The data from finished parts can deviate from above values depending on the manufacturing process and the component geometry.

The data represents our present empirical values. It is incumbent on the person placing the order to examine whether it is suitable for its intended purpose, before using the product. All questions regarding the guarantee of this product are in line with our terms and conditions,

Freudenberg

Freudenberg FST GmbH
 Technology&Innovation
 Material Compliance

Telefon: -

Fax: -

Email: MaterialCompliance@fst.com

Material
71 ACM 112144

black

revision index

1

revision date

9/24/2009

page

3 / 3

inasmuch as statutory provisions do not plan for something else.

Freudenberg

Freudenberg FST GmbH
Technology&Innovation
Material Compliance

Telefon: -

Fax: -

Email: MaterialCompliance@fst.com