



Double wiper AD48

DESCRIPTION


- Double-acting
- Protruding wiper lip
- Without metal angle ring

FUNCTION

- Wiping off impurities on the piston rod during the retraction movement
- Reduction of residual oil film due to second lip
- Pressure relief hole recommended for return of residual oil

PRODUCT ADVANTAGES

- Good wiping properties against dirt
- High wear resistance
- Reliable design with broad application spectrum for moderately demanding applications in general industry
- Long service life
- Good price/performance ratio
- Manufactured by certified external suppliers



APPLICATIONS

- Particularly suitable for applications with heavy contamination
- Mobile hydraulics

CONFORMITY AND CERTIFICATES

- Please consult the material data sheet valid for the respective material for current information on approvals and certificates, as this information depends on the compound and cannot be listed exhaustively here.

DESIGN GUIDELINE

- Installation space cleaned and free of deposits or old packing rings
- Please refer to the technical manual for design guidelines.
- Surface roughness of groove base $R_a \leq 0,4 \mu\text{m}$
- Surface roughness of groove flanks $R_a \leq 4 \mu\text{m}$
- Surface roughness of mating surface $R_a \leq 0,4 \mu\text{m}$

INSTALLATION GUIDELINE

- Installation in axially semi-closed installation spaces
- Deburr sharp edges, provide with seamless chamfers and radii
- Clean the installation space carefully before installation, remove dust, dirt, metal chips, etc.
- Grease mounting surfaces and seal



DICHTOMATIK

Double wiper AD48

STORAGE ADVISE

- Storage temperature <25°C
- No direct heat sources
- No condensation in the storage room
- No exposure to ozone or ionizing radiation
- Recommendations based on the revision of ISO 2230 dated 16.09.1992

Speed [m/s]

TPU

1

Temperature [°C]

TPU

-30...100

The values given are based on a limited number of tests on standard test specimens (2 mm sample plates) from laboratory production. The data determined from finished parts may deviate from the above values depending on the manufacturing process and the part geometry.

The information provided herein is based on laboratory tests and on data sources deemed reliable. It constitutes general, non-binding guideline values and does not represent any guarantee of specific properties or suitability for a particular purpose. The suitability of a product for a specific application depends on the actual operating conditions and a variety of factors. Full testing and performance evaluation of the final product are the responsibility of the user. Freudenberg FST GmbH | www.fst.com



DICHTOMATIK

**FREUDENBERG**
SEALING TECHNOLOGIES