



General Purpose O-Ring Lubricant FN LUBE



DESCRIPTION

- High-performance petroleum-based lubricant
- Ideal for low-pressure pneumatic systems and equipment with reciprocating, low-speed rotary, or oscillating motion

FUNCTION

- Reduces installation friction
- Clings strongly to surfaces and ensures consistent lubrication
- Protects against water exposure

PRODUCT ADVANTAGES

- Reduced risk of seal damage during installation
- More reliable and repeatable assembly processes
- Lower maintenance effort and fewer unplanned failures
- Improved seal longevity in maintenance-intensive applications

APPLICATIONS

- Suitable for various mechanical systems
- Compatible to common elastomers including NBR, FKM, FFKM, Neoprene, Polyurethane and HNBR
- Wide temperature range (-14°F to 176°F)

CONFORMITY AND CERTIFICATES

- Please consult the material data sheet valid for the respective material for current information on approvals and certificates, as this information depends on the compound and cannot be listed exhaustively here.

STORAGE ADVISE

- Storage temperature <25°C
- No direct heat sources
- No direct sunlight
- No condensation in the storage room
- No exposure to ozone or ionizing radiation
- Recommendations based on the revision of ISO 2230 dated 16.09.1992

The information provided herein is based on laboratory tests and on data sources deemed reliable. It constitutes general, non-binding guideline values and does not represent any guarantee of specific properties or suitability for a particular purpose. The suitability of a product for a specific application depends on the actual operating conditions and a variety of factors. Full testing and performance evaluation of the final product are the responsibility of the user. Freudenberg FST GmbH | www.fst.com